

MAN TGX 18.440 4X2 LLS

SH03241022



Price **5,990 EUR** (net)
7,248 EUR (gross)
 Offer Date 12.08.2025

Body type	Tractor unit
1st reg.	01/2014
Power	324kW (441 HP)
Mileage	1140140 km
Storage location	Otopeni - MHS Truck Service

BASIC DATA

Brand	MAN
Model serie	TGX
Model variant	TGX TG2
Body type	Tractor unit
Colours	white
Driver's cab	XXL
Berths	2 berths

TECHNICAL DATA

Power	324 kW (441 HP)
Fuel	Diesel
Gearbox type	Manual
Wheel drive	4x2
Suspension	Air suspension
Axles	2 axles

WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	800 mm
Wheel base	3600 mm
Fuel tank	AdBlue: 100 l Fuel tank: 450 l Fuel tank: 760 l
Emission category	EEV

EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Intarder
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror

Interior

- Board computer
- Multifunctional leather steering wheel
- CB radio
- Digital tachograph
- Sun visor
- Carpet floor covering
- Cooling box

Exterior

- Self-levelling suspension
- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- Fifth wheel
- Spare wheel

Assistance systems

- Cruise control
- MAN BrakeMatic

Comfort

- Adjustable steering column
- Electric window lift 2x
- Automatic climate control
- Driver's armrest
- Electr. lifting sunroof
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Isolated driver's cab
- DC/AC converter

Light and sight

- Fog lights
- Tinted glass
- Cornering light
- Daytime running lights
- Ambient lighting

Audio & communication

- Radio/CD

■ Speed limiter

Wheels and tyres

■ Spare wheel carrier

Equipment packages

■ Aero package

Others

■ front air suspension 8.5 t, rear air suspension 13 t, hub reduction rear axle Hypoid HY-1350, HY axle ratio i 2.71, fuel filter heating, cab tilt mechanism hydraulic/ electric, cab insulation NORDIC, wiring for tank truck to ADR, ADR Typ AT, equipment for dangerous goods to ADR, type OX, supply kit for semitrailer with lifting axle or moving-off aid, trailer socket 24V (7-7-pin)