MAN TGX 18.440 4X2 LLS-U

SH00990526



Body type	Tractor unit
1st reg.	10/2009
Power	324kW (441 HP)
Mileage	1674514 km
Storage location	Otopeni - MHS Truck Service

BASIC DATA

Brand	MAN
Model serie	TGX
Model variant	TGX TG2
Body type	Tractor unit (Mega)
Colours	grey
Driver's cab	XXL
Berths	2 berths

TECHNICAL DATA

Power	324 kW (441 HP)
Fuel	Diesel
Gearbox type	Automatic
Wheel drive	4x2
Suspension	Air suspension
Axles	2 axles

WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	750 mm
Wheel base	3500 mm
Fuel tank	AdBlue: 70 l Fuel tank: 330 l Fuel tank: 595 l
Emission category	EEV

EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Intarder
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror
- Flashing beacon

Comfort

- Adjustable steering column
- Electric window lift 2x
- Automatic climate control
- Front armrest
- Electr. lifting sunroof
- Comfortable front seats
- Additional heating
- Central locking
- Heated drivers seat
- Air-suspended front seats
- Driver's lumbar support
- Isolated driver's cab
- DC/AC converter

Interior

- Board computer
- Multifunctional steering wheel
- CB radio
- Digital tachograph
- Sun visor
- Carpet floor covering
- Cooling box

Light and sight

- Fog lights
- Tinted glass
- Cornering light
- Daytime running lights
- Ambient lighting

Exterior

- Self-levelling suspension
- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- Central lubrication
- Fifth wheel
- Spare wheel
- Cab Suspension
- Working lights

Audio & communication

- Radio/CD: MAN BasicLine 24V
- Mobile phone preparation Bluetooth
- Wireless phone charger

Assistance systems

- Cruise control
- MAN BrakeMatic
- Hill Hold Control HHC
- Speed limiter

Wheels and tyres

- Spare wheel carrier

Equipment packages

- Aero package

Others

- front air suspension 7.5 t, rear air suspension 11.5 t, hub reduction rear axle Hypoid HY-1350, HY axle ratio i 2.71, fuel filter heating, cab insulation NORDIC, cross member for trailer coupling, supply kit for semitrailer with lifting axle or moving-off aid, trailer socket 24V (15-pin), pick-up plate 12 mm