

MAN TGX 18.460 4X2 BLS

SH002110925



Body type	Tractor unit
1st reg.	06/2019
Power	338kW (460 HP)
Mileage	660048 km
Storage location	Otopeni - MHS Truck Service

BASIC DATA

Brand	MAN
Model serie	TGX
Model variant	TGX TG2
Body type	Tractor unit (Standard)
Colours	white
Driver's cab	XL
Berths	1 berth

TECHNICAL DATA

Power	338 kW (460 HP)
Fuel	Diesel
Gearbox type	Automatic
Wheel drive	4x2
Suspension	Leaf air suspension
Axles	2 axles

Price **21,490 EUR** (net)
26,003 EUR (gross)

Offer Date 09.10.2025

WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	800 mm
Wheel base	3600 mm
Fuel tank	AdBlue: 60 l Fuel tank: 580 l
Emission category	Euro6

EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror

Interior

- Board computer
- Multifunctional steering wheel
- Aluminum inlays
- Digital tachograph
- Carpet floor covering
- Cooling box

Audio & communication

- Radio
- Mobile phone preparation Bluetooth
- AUX & USB connector

Exterior

- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- PTO
- Fifth wheel

Comfort

- Adjustable steering column
- Electric window lift 2x
- Air conditioning
- Driver's armrest
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Cup holder front
- Isolated driver's cab
- DC/AC converter

Light and sight

- Fog lights
- Tinted glass
- Headlight range control
- Cornering light
- Daytime running lights

Assistance systems

- Cruise control
- MAN BrakeMatic
- Brake assist: Emergency Brake Assist 2
- Lane-Guard-System LGS
- Hill Hold Control HHC
- Speed limiter

- █ 1x15 pin plug
- █ Cab Suspension
- █ Axle load indicator
- █ Lifting roof (manual)
- █ RIO Box

Wheels and tyres

- █ Spare wheel carrier

Others

- █ front springs parabolic 7.5 t, rear air suspension 13 t, hub reduction rear axle Hypoid HY-1350, HY axle ratio i 2.71, fuel filter heating, cab insulation NORDIC, trailer socket 24V (15-pin), warning sign at rear